



Clay Modeling Products  
Since 1892, the finest name in modeling clay

Chavant, Inc.  
42 West Street  
Red Bank, NJ 07701

1-800-CHAVANT  
Fax: (732) 842-3621  
Internet: <http://www.chavant.com>  
E-mail: [mail@chavant.com](mailto:mail@chavant.com)

---


### MATERIAL SAFETY DATA SHEET

February 26, 2004

---

#### HAZARD RATING

---



---

#### SECTION 1. PRODUCT IDENTIFICATION

---

TRADE NAMES: CM-50, CM-70, DaVinci, H-525, I-305, I-307, J-88, J-525, Professional Plasteline

CHEMICAL NAME: Sulfur-Based Modeling Clay

EMERGENCY PHONE: 1-800-242-8268  
1-732-842-6272

EMERGENCY FAX: 1-732-842-3621

---

#### SECTION 2. HAZARDOUS INGREDIENT INFORMATION

---

This product is not hazardous as defined in 29 CFR 1900.1200. The composition of this clay is a trade secret as allowed by 29 CFR 1910.1200-48. In the event of a medical emergency, compositional information will be provided to a physician or nurse.

Product labeling conforms to ASTM D-4236 (no special label required).

---

SECTION 3.        PHYSICAL AND CHEMICAL DATA

---

Appearance and Odor:    Brown or green, pliable solid, varying degree of odor.

Specific Gravity:        Varies between 1.47 and 1.76 g/cm<sup>3</sup> depending on formula.

Solubility in Water:    Negligible ( <1% )

Evaporation Rate:      N/A

Vapor Pressure:        N/A

Vapor Density:         N/A

Melting Point:         180 - 200 °F

---

SECTION 4.        HEALTH INFORMATION AND PROTECTION

---

NATURE OF HAZARD

EYE CONTACT:         Direct contact may irritate but will not injure eye tissue.

SKIN CONTACT:        Clay is regularly used with no skin protection. Hypersensitive users may experience slight irritation.

INHALATION:         N/A

INGESTION:            May induce laxative effects.

FIRST AID

EYE CONTACT:         Flush with water.

SKIN CONTACT:        Modeling clay is normally used with no skin protection. If irritation appears, it is an allergic reaction and use should be discontinued.

INHALATION:         Normally not required.

INGESTION:            Normally not required.

---

SECTION 5.        FIRE AND EXPLOSION HAZARD

---

FLASHPOINT:            > 200 °F.

FLAMMABLE LIMITS:    N/A

SPECIAL FIRE FIGHTING INFORMATION:    Firefighters should use self-contained breathing apparatus to avoid exposure to smoke and vapor. A component, SULFUR, often burns in air to form Sulfur Dioxide.

