
MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION OF SUBSTANCE & COMPANY PREPARING INFORMATION

Identity: HG-13 Banana

Manufacturer's Name: Minnesota Clay

Address: 2960 Niagara Lane, Plymouth MN 55447

Tel Phone: (763) 432-0875

Emergency Tel: None

Date Prepared: July 29, 2011

Replaces MSDS dated: N/A

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	EXPOSURE LIMITS (mg/m ³)		LD ₅₀ mg/kg	LC ₅₀ mg/m ³
		PEL	TLV		
Clay/Kaolin	1332-58-7	15	2	NA	NA
Silica (Quartz)	14808-60-7	<u>10mg/m³</u> %Silica+2	0.025	NA	NA
Calcium Carbonate	1317-65-3	15	NA	6540	NA
Zirconium	14940-68-2	NA	NA	NA	NA
Pigments	Varies	NA	NA	NA	NA

SECTION 3 - HAZARD IDENTIFICATION

Primary Route of Entry - Inhalation (dry form only), ingestion and dermal.

Hazards - May cause skin and eye irritation, Lung effects including cancer, silicosis

Silica, Crystalline (Quartz)

A single exposure will not result in serious adverse health effects.

Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death. Crystalline silica (quartz) inhaled from occupational sources is classified as carcinogenic to humans. There are some studies that show excess numbers of cases of scleroderma and other connective

tissue disorders in workers exposed to respirable crystalline silica. Silicosis increases the risk of tuberculosis. Some studies that show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

Calcium Carbonate

Overexposure may result in irritation to eyes, skin and respiratory system. Chronic exposure may result in hyperclacemica, alkalosis, and renal impairment. Animal studies suggest that inhalation may enhance susceptibility to respiratory infection.

Zirconium or Zirconium Compounds

Skin, lung granulomas; in animals: irritation skin, mucous membrane; X-ray evidence of retention in lungs.

Pigments (Stains)

Contains pigments which are produced from various metal salts, and/or other organic chemicals. Many of these pigments are in the form of spinel, which are formed by the reaction of these different metal salts at high temperature into essentially insoluble homogeneous pigment crystals. Spinel are considered of less hazardous than the individual metals they contain The pigments used may contain one or more of the following: silica (quartz), cobalt, vanadium, copper, iron, manganese, chromium and cadmium (encapsulated).

SECTION 4 - FIRST-AID MEASURES

Inhalation - Remove from exposure.

Dermal - Wash skin with soap and water.

Eye - Flush eyes with large quantities of water for at least 15 minutes. If irritation is present after washing, contact a physician.

Ingestion- Do not induce vomiting, contact a physician.

SECTION 5 - FIRE-FIGHTING MEASURES

Special Fire-Fighting Procedure - None

Unusual Fire or Explosion Hazards - None

Extinguishing Media - None
Hazardous Combustion Products –Unknown

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Procedures for Leaks or Spills - place in suitable container, and provide adequate ventilation. Wear personnel protective equipment (Goggles, glove, personal protective clothing).

SECTION 7 - HANDLING AND STORAGE

Engineer Control – use adequate ventilation

Procedure/Equipment - no specific requirement. See personal protective equipment.

Work Practices - use with adequate ventilation, avoid skin, eye and inhalation contact, wash hands

Storage - Store in tightly closed container. Store in a cool well-ventilated area.

SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering Measures – provide adequate ventilation

Personal Protective Equipment - wear chemical safety goggles, protective chemical resistant gloves, appropriate protective clothing

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance - Powder

Partition Coefficient - N/A

Explosive Properties - N/A

pH - N/A

Odor and Odor Threshold - N/A

Oxidizing Properties - N/A

Boiling Point - N/A

Melting/Softening Point - None

Solubility in Water - No

Freezing Point - N/A

Vapor Pressure - N/A

Specific Gravity - N/A

Percent Volatile - N/A

Flash Point - N/A

Vapor Density - N/A

Flammable Limits - N/A

Applicable Evaporation Rate - N/A

Auto-Ignition Temperature - N/A

SECTION 10 - STABILITY AND REACTIVITY

Stability - Unknown

Hazardous Polymerization - None

Hazardous Decomposition Products - None

Conditions to Avoid - None

Incompatibility – Unknown

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazard to Humans - There is no toxicity data on this mixture. Likely to be a skin and eye irritant. Inhalation of dust may cause lung effects.

Animal Experiment - There is no toxicity data on this mixture

Acute – Likely to be a skin and eye irritant

Chronic/Other - Inhalation may cause lung effects. Contains quartz, which can cause silicosis and is a potential carcinogen.

SECTION 12 - ECOLOGICAL INFORMATION

No specific information available.

SECTION 13 - DISPOSAL INFORMATION

Dispose according to local regulations. No specific information available.

SECTION 14 - TRANSPORTATION INFORMATION

No specific information available.

SECTION 15 - REGULATORY INFORMATION

Ingredients are listed on TSCA, DSL and EINECS inventories.

Quartz is listed on IARC, NTP, OSHA and/or Calif. Prop 65 cancer lists.

No specific other information available.

SECTION 16 - OTHER INFORMATION

Conforms to D 4236

No other specific information available.